

表 8

型号	功率 Kw	转速 r/min	效率 %		功率 因数 COS φ	电流 (380V) A		转矩			噪声 dB (A) L _W /L _P	转动 惯量 kg. m2	重量 kg
			100% 负载	75% 负载		额定电 流 I _N (A)	堵转 电流 额定 电流	额定转 矩 T _N (Nm)	堵转 转矩 额定 转矩	最大 转矩 额定 转矩			
同步转速 3000r/min													
YBX3-80M1-2	0.75	2825	80.7	80.7	0.83	1.70	6.8	2.54	2.3	2.3	64/56	0.005	43
YBX3-80M2-2	1.1	2825	82.7	82.7	0.83	2.43	7.3	3.72	2.3	2.3	64/56	0.007	46
YBX3-90S-2	1.5	2840	84.2	84.2	0.84	3.22	7.6	5.04	2.3	2.3	72/64	0.009	52
YBX3-90L-2	2.2	2840	85.9	85.9	0.85	4.58	7.8	7.40	2.3	2.3	72/64	0.017	55
YBX3-100L-2	3	2880	87.1	87.1	0.87	6.02	8.1	9.95	2.3	2.3	76/68	0.03	71
YBX3-112M-2	4	2890	88.1	88.1	0.87	7.93	8.3	13.22	2.2	2.3	77/69	0.063	98
YBX3-132S1-2	5.5	2900	89.2	89.2	0.88	10.65	8.0	18.11	2.2	2.3	80/72	0.073	115
YBX3-132S2-2	7.5	2900	90.1	90.1	0.88	14.37	7.8	24.70	2.2	2.3	80/72	0.21	125
YBX3-160M1-2	11	2930	91.2	91.2	0.88	20.82	7.9	35.85	2.2	2.3	82/74	0.25	177
YBX3-160M2-2	15	2930	91.9	91.9	0.88	28.18	8.0	48.89	2.2	2.3	82/74	0.31	191
YBX3-160L-2	18.5	2930	92.4	92.4	0.88	34.57	8.1	60.30	2.2	2.3	82/74	0.37	212
YBX3-180M-2	22	2940	92.7	92.7	0.89	40.52	8.2	71.46	2.2	2.3	85/77	0.63	278
YBX3-200L1-2	30	2950	93.3	93.3	0.89	54.89	7.5	97.12	2.2	2.3	87/79	0.73	366
YBX3-200L2-2	37	2950	93.7	93.7	0.89	67.41	7.5	119.78	2.2	2.3	87/79	1.28	385
YBX3-225M-2	45	2970	94	94	0.89	81.73	7.6	144.70	2.2	2.3	89/82	1.55	460
YBX3-250M-2	55	2970	94.3	94.3	0.89	99.57	7.6	176.85	2.2	2.3	89/82	1.89	560
YBX3-280S-2	75	2970	94.7	94.7	0.89	135.20	6.9	241.16	2.0	2.3	91/83	2.02	730
YBX3-280M-2	90	2970	95	95	0.89	161.73	7.0	289.39	2.0	2.3	91/83	2.26	850
YBX3-315S-2	110	2980	95.2	95.2	0.89	197.26	7.1	352.52	2.0	2.2	95/85	2.42	1265
YBX3-315M-2	132	2980	95.4	95.4	0.89	236.21	7.1	423.02	2.0	2.2	95/85	2.726	1334
YBX3-315L1-2	160	2980	95.6	95.6	0.89	285.72	7.1	512.75	2.0	2.2	95/85	3.22	1553
YBX3-315L-2	185	2980	95.7	95.7	0.9	326.35	7.1	592.87	2.0	2.2	95/85	3.41	1725
YBX3-315L2-2	200	2980	95.8	95.8	0.9	352.44	7.1	640.94	2.0	2.2	95/85	3.86	1840
YBX3-355S1-2	185	2980	95.8	95.8	0.9	326.01	7.1	592.87	2.0	2.2	98/88	4.82	1944
YBX3-355S2-2	200	2980	95.8	95.8	0.9	352.44	7.1	640.94	2.0	2.2	98/88	5.46	1944
YBX3-355M1-2	220	2980	95.8	95.8	0.9	387.69	7.1	705.03	2.0	2.2	98/88	6.22	2116
YBX3-355M2-2	250	2980	95.8	95.8	0.9	440.56	7.1	801.17	2.0	2.2	98/88	6.54	2415
YBX3-355L1-2	280	2980	95.8	95.8	0.9	493.42	7.1	897.32	2.0	2.2	98/88	6.95	2599
YBX3-355L2-2	315	2980	95.8	95.8	0.9	555.10	7.1	1009.4	2.0	2.2	98/88	7.06	3260
YBX3-4001-2	355	2980	95.8	95.8	0.9	625.59	7.1	1137.6	1.1	2.2	105/95	6.8	3370
YBX3-4002-2	400	2980	95.8	95.8	0.9	704.89	7.1	1281.8	1.1	2.2	105/95	8.2	3450
YBX3-4003-2	450	2980	95.8	95.8	0.9	793.00	7.1	1442.1	1.1	2.2	105/95	9.3	3540
YBX3-4004-2	500	2980	95.8	95.8	0.9	881.11	7.1	1602.3	1.1	2.2	105/95	10.3	3620
YBX3-4005-2	560	2980	95.8	95.8	0.9	986.84	7.1	1794.6	1.1	2.2	105/95	12.5	3690

注:1. 当额定电压不是 380V 时, 额定电流按 $I_N=I(380V)*380/U_N$ 。 2. 效率、功率因数为标称值。 3. 机座号 400 及以上 2 极电机为单向风扇时的噪声。

10

注:1. 当额定电压不是 380V 时, 额定电流按 $I_N = I(380V) \times 380 / U_N$ 。 2. 效率、功率因数为标称值。 3. 机座号 400 及以上 2 极电机为单向风扇时的噪声。

表 8 (续)

型号	功率 Kw	转速 r/min	效率 %		功率 因数 COS Φ	电流 (380V)A		转矩			噪声 dB(A) Lw/Lp	转动 惯量 kg. m2	重量 kg
			100% 负载	75% 负载		额定电 流 IN A	堵 转 电流 额定 电流	额定转 矩 TN (Nm)	堵转 转矩	最大 转矩			
同步转速 1500r/min													
YBX3-80M1-4	0.55	1390	76.5	76.5	0.75	1.46	6.3	3.78	2.3	2.3	58/50	0.007	43
YBX3-80M2-4	0.75	1390	82.5	82.5	0.75	1.84	6.5	5.15	2.3	2.3	58/50	0.012	46
YBX3-90S-4	1.1	1400	84.1	84.1	0.75	2.65	6.6	7.50	2.3	2.3	61/53	0.015	51
YBX3-90L-4	1.5	1400	85.3	85.3	0.75	3.56	6.9	10.23	2.3	2.3	61/53	0.031	55
YBX3-100L1-4	2.2	1420	86.7	86.7	0.81	4.76	7.5	14.80	2.3	2.3	64/56	0.039	71
YBX3-100L2-4	3	1420	87.7	87.7	0.82	6.34	7.6	20.18	2.3	2.3	64/56	0.059	98
YBX3-112M-4	4	1440	88.6	88.6	0.82	8.37	7.7	26.53	2.3	2.3	65/57	0.113	115
YBX3-132S-4	5.5	1440	89.6	89.6	0.82	11.37	7.5	36.48	2.0	2.3	71/63	0.167	125
YBX3-132M-4	7.5	1440	90.4	90.4	0.83	15.19	7.4	49.74	2.0	2.3	71/63	0.36	127
YBX3-160M-4	11	1460	91.4	91.4	0.85	21.51	7.5	71.95	2.2	2.3	74/66	0.42	189
YBX3-160L-4	15	1460	92.1	92.1	0.85	29.11	7.5	98.12	2.2	2.3	74/66	0.68	212
YBX3-180M-4	18.5	1470	92.6	92.6	0.86	35.30	7.7	120.19	2.2	2.3	76/68	0.072	275
YBX3-180L-4	22	1470	93	93	0.86	41.79	7.8	142.93	2.2	2.3	76/68	0.81	300
YBX3-200L-4	30	1470	93.6	93.6	0.86	56.63	7.2	194.90	2.2	2.3	79/71	1.21	423
YBX3-225S-4	37	1480	93.9	93.9	0.86	69.62	7.3	238.75	2.2	2.3	81/73	1.85	460
YBX3-225M-4	45	1480	94.2	94.2	0.86	84.40	7.4	290.37	2.2	2.3	81/73	2.32	477
YBX3-250M-4	55	1480	94.6	94.6	0.86	102.72	7.4	354.90	2.2	2.3	82/74	2.86	676
YBX3-280S-4	75	1480	95	95	0.87	137.88	6.7	483.95	2.0	2.3	85/77	3.34	782
YBX3-280M-4	90	1485	95.2	95.2	0.87	165.10	6.9	578.79	2.0	2.3	85/77	4.68	915
YBX3-315S-4	110	1485	95.4	95.4	0.87	201.37	6.9	707.41	2.0	2.2	91/79	4.96	1323
YBX3-315M-4	132	1485	95.6	95.6	0.88	238.40	6.9	848.89	2.0	2.2	91/79	5.22	1380
YBX3-315L1-4	160	1485	95.8	95.8	0.88	288.36	6.9	1028.96	2.0	2.2	91/79	5.43	1518
YBX3-315L-4	185	1485	95.9	95.9	0.89	329.33	6.9	1189.73	2.0	2.2	91/79	5.62	1633
YBX3-315L2-4	200	1485	96.0	96.0	0.89	355.66	6.9	1286.20	2.0	2.2	91/79	6.45	1725
YBX3-355S1-4	185	1488	96.0	96.0	0.89	328.99	6.9	1187.33	2.0	2.2	94/82	6.56	1955
YBX3-355S2-4	200	1488	96.0	96.0	0.9	351.71	6.9	1283.60	2.0	2.2	94/82	6.88	2070
YBX3-355M1-4	220	1488	96.0	96.0	0.9	386.88	6.9	1411.96	2.0	2.2	94/82	7.22	2231
YBX3-355M2-4	250	1488	96.0	96.0	0.9	439.64	6.9	1604.50	2.0	2.2	94/82	7.46	2392
YBX3-355L1-4	280	1488	96.0	96.0	0.9	492.39	6.9	1797.04	2.0	2.2	94/82	7.68	2599
YBX3-355L2-4	315	1488	96.0	96.0	0.9	553.94	6.9	2021.67	2.0	2.2	94/82	7.8	2990
YBX3-4001-4	355	1488	96.0	96.0	0.9	624.29	6.5	2278.39	1.0	2.2	105/93	8.89	3260
YBX3-4002-4	400	1488	96.0	96.0	0.9	703.42	6.5	2567.20	1.0	2.2	105/93	10.12	3400
YBX3-4003-4	450	1488	96.0	96.0	0.9	791.35	6.5	2888.10	1.0	2.2	105/93	11.64	3520
YBX3-4004-4	500	1488	96.0	96.0	0.9	879.28	6.5	3209.01	1.0	2.2	105/93	12.73	3620
YBX3-4005-4	560	1488	96.0	96.0	0.9	984.79	6.5	3594.09	1.0	2.2	105/93	13.2	3690
注: 1. 当额定电压不是 380V 时, 额定电流按 IN=I (380V)*380/UN。 2. 效率、功率因数为标称值。													

注: 1. 当额定电压不是 380V 时, 额定电流按 $I_N = I(380V) \times 380 / U_N$ 。 2. 效率、功率因数为标称值。

表 8 (续)

型号	功率 Kw	转速 r/min	效率 %		功率 因数 COS φ	电流 (380V) A		转矩			噪声 dB (A) Lw/Lp	转动 惯量 kg. m2	重量 kg
			100% 负载	75% 负载		额定电 流 IN (A)	堵转 电流 额定 电流	额定转 矩 TN (Nm)	堵转 转矩	最大 转矩			
									额定 转矩	额定 转矩			
同步转速 1000r/min													
YBX3-80M1-6	0.37	910	71.4	71.4	0.71	1.11	4.7	3.88	1.9	2.0	54/46	0.039	46
YBX3-80M2-6	0.55	910	74.2	74.2	0.72	1.56	4.7	5.77	1.9	2.1	54/46	0.059	51
YBX3-90S-6	0.75	910	78.9	78.9	0.73	1.98	5.8	7.87	2.1	2.1	57/49	0.113	69
YBX3-90L-6	1.1	910	81	81	0.73	2.83	5.9	11.54	2.1	2.1	57/49	0.167	71
YBX3-100L-6	1.5	940	82.5	82.5	0.74	3.73	6.0	15.24	2.1	2.1	61/53	0.36	89
YBX3-112M-6	2.2	940	84.3	84.3	0.74	5.36	6.0	22.35	2.1	2.1	65/57	0.42	115
YBX3-132S-6	3	960	85.6	85.6	0.74	7.20	6.2	29.84	2.0	2.1	69/62	0.68	122
YBX3-132M1-6	4	960	86.8	86.8	0.75	9.34	6.8	39.79	2.0	2.1	69/62	0.072	127
YBX3-132M2-6	5.5	960	88	88	0.78	12.17	7.1	54.71	2.0	2.1	69/62	0.81	130
YBX3-160M-6	7.5	970	89.1	89.1	0.79	16.19	6.7	73.84	2.1	2.1	70/62	1.21	185
YBX3-160L-6	11	970	90.3	90.3	0.79	23.43	6.9	108.30	2.1	2.1	70/62	1.32	222
YBX3-180L-6	15	970	91.2	91.2	0.81	30.85	7.2	147.68	2.0	2.1	70/62	1.62	280
YBX3-200L1-6	18.5	970	91.7	91.7	0.82	37.38	7.2	182.14	2.1	2.1	76/68	1.84	366
YBX3-200L2-6	22	970	92.2	92.2	0.82	44.21	7.3	216.60	2.1	2.1	76/68	2.43	385
YBX3-225M-6	30	980	92.9	92.9	0.84	58.41	7.1	292.35	2.0	2.1	76/68	2.68	471
YBX3-250M-6	37	980	93.3	93.3	0.85	70.89	7.1	360.56	2.1	2.1	78/70	3.46	633
YBX3-280S-6	45	980	93.7	93.7	0.85	85.85	7.2	438.52	2.1	2.0	80/72	3.97	750
YBX3-280M-6	55	980	94.1	94.1	0.85	104.48	7.2	535.97	2.1	2.0	80/72	4.57	859
YBX3-315S-6	75	985	94.6	94.6	0.85	141.72	6.7	727.16	2.0	2.0	85/73	4.83	1242
YBX3-315M-6	90	985	94.9	94.9	0.85	169.52	6.7	872.59	2.0	2.0	85/73	5.32	1311
YBX3-315L1-6	110	985	95.1	95.1	0.86	204.35	6.7	1066.50	2.0	2.0	85/73	5.95	1506
YBX3-315L2-6	132	985	95.4	95.4	0.86	244.45	6.7	1279.80	2.0	2.0	85/73	7.32	1610
YBX3-355S-6	160	985	95.6	95.6	0.87	292.29	6.7	1551.27	2.0	2.0	91/79	7.89	1897
YBX3-355M1-6	185	985	95.7	95.7	0.87	337.61	6.7	1793.65	2.0	2.0	91/79	8.17	2024
YBX3-355M2-6	200	985	95.8	95.8	0.87	364.60	6.7	1939.09	2.0	2.0	91/79	8.25	2265
YBX3-355L1-6	220	985	95.8	95.8	0.87	401.06	6.7	2132.99	2.0	2.0	91/79	8.36	2461
YBX3-355L2-6	250	985	95.8	95.8	0.88	450.57	6.7	2423.86	2.0	2.0	91/79	8.38	2587
YBX3-4001-6	280	985	95.8	95.8	0.88	504.64	6.7	2714.72	1.0	2.0	92/80	12.52	3260
YBX3-4002-6	315	985	95.8	95.8	0.88	567.72	6.7	3054.06	1.0	2.0	92/80	13.34	3400
YBX3-4003-6	355	985	95.8	95.8	0.88	639.81	6.7	3441.88	1.0	2.0	92/80	13.95	3520
YBX3-4004-6	400	985	95.8	95.8	0.88	720.91	6.7	3878.17	1.0	2.0	92/80	14.32	3620
YBX3-4005-6	450	985	95.8	95.8	0.88	811.02	6.7	4362.94	1.0	2.0	92/80	15.46	3690
注: 1. 当额定电压不是 380V 时, 额定电流按 IN=I (380V)*380/UN。 2. 效率、功率因数为标称值。													

表 8 (续)

型号	功率 Kw	转速 r/min	效率 %		功率 因数 COS Φ	电流 (380V) A		转矩			噪声 dB (A) Lw/Lp	转动 惯量 kg. m2	重量 kg
			100% 负载	75% 负载		额定电 流 IN (A)	堵转 电流	额定转 矩 TN (Nm)	堵转 转矩	最大 转矩			
同步转速 750r/min													
YBX3-80M1-8	0.18	710	51	51	0.61	0.88	3.3	2.42	1.8	1.9	52/44	0.16	43
YBX3-80M2-8	0.25	710	54	54	0.61	1.15	3.3	3.36	1.8	1.9	52/44	0.18	46
YBX3-90S-8	0.37	710	62	62	0.62	1.46	4	4.98	1.8	1.9	56/48	0.2	52
YBX3-90L-8	0.55	710	63	63	0.63	2.11	4	7.40	1.8	2.0	56/458	0.22	55
YBX3-100L1-8	0.75	710	70	70	0.67	2.43	4	10.09	1.8	2.0	59/51	0.24	72
YBX3-100L2-8	1.1	710	72	72	0.69	3.36	5	14.80	1.8	2.0	59/51	0.25	90
YBX3-112M-8	1.5	710	74	74	0.7	4.40	5	20.18	1.8	2.0	61/53	0.28	116
YBX3-132S-8	2.2	710	79	79	0.71	5.96	6	29.59	1.8	2.0	64/56	0.3	123
YBX3-132M-8	3	710	80	80	0.73	7.81	6	40.35	1.8	2.0	64/56	0.32	128
YBX3-160M1-8	4	720	81	81	0.73	10.28	6	53.06	1.9	2.0	68/60	0.46	162
YBX3-160M2-8	5.5	720	83	83	0.74	13.61	6	72.95	1.9	2.0	68/60	0.61	176
YBX3-160L-8	7.5	720	85.5	85.5	0.75	17.77	6	99.48	1.9	2.0	68/60	1.06	212
YBX3-180L-8	11	730	87.5	87.5	0.75	25.47	6.5	143.90	2	2.0	70/62	1.6	268
YBX3-200L-8	15	730	88	88	0.76	34.08	6.6	196.23	2	2.0	73/65	2.28	282
YBX3-225S-8	18.5	730	90	90	0.76	41.09	6.6	242.02	1.9	2.0	73/65	2.74	431
YBX3-225M-8	22	730	90.5	90.5	0.78	47.35	6.6	287.81	1.9	2.0	73/65	3.67	454
YBX3-250M-8	30	730	91	91	0.79	63.40	6.5	392.47	1.9	2.0	75/67	5.16	639
YBX3-280S-8	37	740	91.5	91.5	0.79	77.77	6.6	477.50	1.9	2.0	76/67	5.82	705
YBX3-280M-8	45	740	92	92	0.79	94.07	6.6	580.74	1.9	2.0	76/67	6.74	815
YBX3-315S-8	55	740	92.8	92.8	0.81	111.17	6.6	709.80	1.8	2.0	82/70	7.35	1058
YBX3-315M-8	75	740	93.5	93.5	0.81	150.46	6.2	967.91	1.8	2.0	82/70	8.79	1265
YBX3-315L1-8	90	740	93.8	93.8	0.82	177.78	6.4	1161.49	1.8	2.0	82/70	9.18	1288
YBX3-315L2-8	110	740	94	94	0.82	216.83	6.4	1419.59	1.8	2.0	82/70	10.19	1495
YBX3-355S-8	132	740	93.7	93.7	0.82	261.03	6.4	1703.51	1.8	2.0	89/77	11.24	1886
YBX3-355M-8	160	740	94.2	94.2	0.82	314.72	6.4	2064.86	1.8	2.0	89/77	12.48	2093
YBX3-355L1-8	185	740	94.2	94.2	0.82	363.89	6.4	2387.50	1.8	2.0	89/77	13.56	2415
YBX3-355L2-8	200	740	94.5	94.5	0.83	387.43	6.4	2581.08	1.8	2.0	89/77	13.84	2450
YBX3-4001-8	220	740	95	95	0.84	418.88	6.5	2839.19	1.2	2.0	91/79	16.68	3260
YBX3-4002-8	250	740	95	95	0.84	476.00	6.5	3226.35	1.2	2.0	91/79	17.35	3400
YBX3-4003-8	280	740	95	95	0.84	533.12	6.5	3613.51	1.2	2.0	91/79	18.9	3520
YBX3-4004-8	315	740	95	95	0.84	599.76	6.5	4065.20	1.2	2.0	91/79	20.34	3620
YBX3-4005-8	355	740	95.1	95.1	0.84	675.21	6.5	4581.42	1.2	2.0	91/79	22.67	3690
注: 1. 当额定电压不是 380V 时, 额定电流按 IN=I (380V)*380/UN。 2. 效率、功率因数为标称值。													

表 8 (续)

型号	功率 Kw	转速 r/min	效率 %		功率 因数 COS φ	电流 (380V)A		转矩			噪声 dB(A) Lw/Lp	转动 惯量 kg. m2	重量 kg
			100% 负载	75% 负载		额定电 流 IN (A)	堵转 电流 额定 电流	额定转 矩 TN (Nm)	堵转 转矩	最大 转矩			
									额定 转矩	额定 转矩			
同步转速 600r/min													
YBX3-250M-10	18.5	585	90	90	0.72	43.38	6.2	302.01	1.8	2.0	75/67	5.16	659
YBX3-250M-10	22	585	90	90	0.72	51.58	6.2	359.15	1.8	2.0	75/67	5.16	659
YBX3-280S-10	30	585	90.7	90.7	0.73	68.84	6.2	489.74	1.6	2.0	75/67	5.82	705
YBX3-280M-10	37	585	90.7	90.7	0.75	82.64	6.2	604.02	1.6	2.0	75/67	6.74	815
YBX3-315S-10	45	587	91.5	91.5	0.75	99.63	6.2	732.11	1.5	2.0	82/74	9.35	920
YBX3-315M-10	55	587	92	92	0.75	121.11	6.2	894.80	1.5	2.0	82/74	10.79	1100
YBX3-315L1-10	75	587	92.5	92.5	0.76	162.10	5.8	1220.19	1.5	2.0	82/74	11.18	1120
YBX3-315L2-10	90	587	93	93	0.77	190.96	5.9	1464.22	1.5	2.0	82/74	11.67	1300
YBX3-355S-10	90	587	93.2	93	0.77	190.55	5.9	1464.22	1.5	2.0	89/77	12.24	1640
YBX3-355M1-10	110	587	93.5	93.2	0.78	229.17	6.0	1789.61	1.3	2.0	89/77	13.48	1820
YBX3-355M2-10	132	587	93.5	93.5	0.78	275.00	6.0	2147.53	1.3	2.0	89/77	14.28	2100
YBX3-355L1-10	160	587	93.5	93.5	0.78	333.34	6.0	2603.07	1.3	2.0	89/77	15.3	2200
YBX3-355L2-10	185	587	93.5	93.5	0.78	385.42	6.0	3009.80	1.3	2.0	89/77	16.32	2260
YBX3-4001-10	200	587	93.8	93.8	0.80	404.95	6.0	3253.83	1.0	2.0	91/79	17.88	3260
YBX3-4002-10	220	587	93.8	93.8	0.80	445.45	6.0	3579.22	1.0	2.0	91/79	18.95	3400
YBX3-4003-10	250	587	93.8	93.8	0.80	506.19	6.0	4067.29	1.0	2.0	91/79	19.65	3520
YBX3-4004-10	280	587	93.8	93.8	0.80	566.94	6.0	4555.37	1.0	2.0	91/79	21.88	3620
YBX3-4005-10	315	587	93.8	93.8	0.80	637.80	6.0	5124.79	1.0	2.0	91/79	23.74	3690
同步转速 500r/min													
YBX3-250M-12	18.5	480	88	88	0.67	47.67	5.5	368.07	1.5	2.0	75/67	5.16	625
YBX3-280S-12	22	480	88	88	0.69	55.05	5.5	437.71	1.5	2.0	75/68	5.82	720
YBX3-280M-12	30	480	89	89	0.72	71.13	5.5	596.88	1.5	2.0	75/69	6.74	940
YBX3-315S-12	37	485	92	92	0.72	84.87	6.5	728.56	1.2	2.0	82/74	7.35	1120
YBX3-315M-12	45	485	92	92	0.72	103.22	6.5	886.08	1.2	2.0	82/74	8.79	1120
YBX3-315L1-12	55	485	92	92	0.73	124.43	6.5	1082.99	1.2	2.0	82/74	9.18	1300
YBX3-315L2-12	75	485	93	93	0.73	167.85	6.5	1476.80	1.2	2.0	82/74	10.19	1640
YBX3-355S-12	75	485	93	93	0.73	167.85	6.5	1476.80	1.2	2.0	89/77	11.24	1820
YBX3-355M1-12	90	485	93	93	0.75	196.05	6.5	1772.16	1.2	2.0	89/77	12.48	2100
YBX3-355M2-12	110	485	93.2	93	0.75	239.10	6.5	2165.98	1.2	2.0	89/77	12.83	2180
YBX3-355L1-12	132	485	93.2	93.5	0.75	286.92	6.5	2599.18	1.2	2.0	89/77	13.56	2200
YBX3-355L2-12	160	485	93.2	93.5	0.78	334.41	6.5	3150.52	1.2	2.0	89/77	13.72	2300
YBX3-4001-12	185	485	93.5	93.5	0.80	375.78	5.5	3642.78	1.0	1.8	91/79	20.54	3400
YBX3-4002-12	200	485	93.5	93.5	0.80	406.25	5.5	3938.14	1.0	1.8	91/79	22.67	3520
YBX3-4003-12	220	485	93.5	93.5	0.80	446.88	5.5	4331.96	1.0	1.8	91/79	24.74	3620
YBX3-4004-12	250	485	93.5	93.5	0.81	501.55	5.5	4922.68	1.0	1.8	91/79	26.86	3690
YBX3-4005-12	280	485	93.5	93.5	0.81	561.73	5.5	5513.40	1.0	1.8	91/79	26.86	3850
注: 1. 当额定电压不是 380V 时, 额定电流按 $IN=I(380V)*380/UN$ 。 2. 效率、功率因数为标称值。													

注:1. 当额定电压不是 380V 时, 额定电流按 $I_N = I(380V) \times 380 / U_N$ 。 2. 效率、功率因数为标称值。